

GREENSCREEN REVIVE® 1%

Professional Architectural Specification

AVAILABLE COLORWAYS

Dusk

Linen

Mushroom

Onyx

Pewter

Sand

Stone

Suede

TECHNICAL SPECIFICATIONS

DESCRIPTION

The **GreenScreen Revive® 1%** represents the pinnacle of sustainable solar control. Made from high-quality recycled materials, this fabric allows designers to achieve high-performance solar management without compromising environmental values. The 1% openness factor is ideal for spaces requiring significant glare reduction and thermal protection while maintaining a soft, textile aesthetic.

Fenestration Data

Color Name	Thermal – Total Solar			Rv (%)	Tv (%)	SHGC % Improvement (Commercial)	SHGC (Residential)
	Rs (%)	As (%)	Ts (%)				
Onyx	34	49	17	11	5	18	0.51
Stone	52	24	24	44	17	34	0.42
Pewter	43	19	38	25	8	24	0.46
Dusk	36	14	50	11	2	18	0.50
Suede	39	42	19	20	7	21	0.48
Mushroom	46	20	34	32	10	29	0.45
Linen	58	17	25	55	20	42	0.38
Sand	61	13	26	60	23	45	0.36

KEY CHARACTERISTICS

- 89% Recycled Content for superior sustainability
- Maximum UV Blockage (99%) for interior protection
- Antimony and Halogen Free Flame Retardant
- Wide 118" format for large windows

TECHNICAL DATA

Fire Classifications NFPA 701 TM#1, California U.S. Title 19, CAN/ULC-S109
 Fungal Resistance ASTM G21
 Acoustical Performance NRC: 0.20, SAA: 0.22
 Environmental Benefits RoHS Lead Free, GREENGUARD Gold, Cradle to Cradle Bronze, Declare Label

TECHNICAL SPECS

Information for this section is coming soon. Please contact us to request this data.

CARE & HANDLING

Regular light dusting with a feather duster is suggested. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. Alternatively, dirt and debris can be blown away using compressed air or a hand-held air dryer on the cool setting. A dry chemical sponge may also be used for spot cleaning.