

GREENSCREEN REVIVE® 5%

Professional Architectural Specification

AVAILABLE COLORWAYS

Dusk

Linen

Mushroom

Onyx

Pewter

Sand

Stone

Suede

TECHNICAL SPECIFICATIONS

DESCRIPTION

The **GreenScreen Revive® 5%** offers a sustainable path to solar management, combining architectural performance with environmental stewardship. Utilizing 89% recycled polyester, this fabric reduces waste while providing a clear view to the outdoors. The 5% openness factor is the most popular choice for general office and living areas where light filtering and view-through are desired alongside solar heat protection.

Fenestration Data

Color Name	Thermal – Total Solar			Rv (%)	Tv (%)	SHGC % Improvement (Commercial)	SHGC (Residential)
	Rs (%)	As (%)	Ts (%)				
Onyx	31	47	22	10	9	16	0.56
Stone	49	24	27	43	20	32	0.45
Pewter	37	37	26	23	14	21	0.52
Dusk	31	47	22	10	8	16	0.56
Suede	35	40	25	18	13	18	0.53
Mushroom	42	31	27	31	18	24	0.49
Linen	52	16	32	50	28	34	0.44
Sand	54	11	35	54	33	37	0.43

KEY CHARACTERISTICS

- 89% Recycled Content for superior sustainability
- Exceptional outward visibility with 5% openness
- Antimony and Halogen Free Flame Retardant
- Wide 118? format for large windows

TECHNICAL DATA

Fire Classifications NFPA 701 TM#1, California U.S. Title 19, CAN/ULC-S109
 Fungal Resistance ASTM G21
 Acoustical Performance NRC: 0.15, SAA: 0.14
 Environmental Benefits RoHS Lead Free, GREENGUARD Gold, Cradle to Cradle Bronze, Declare Label

TECHNICAL SPECS

Information for this section is coming soon. Please contact us to request this data.

CARE & HANDLING

Regular light dusting with a feather duster is suggested. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric. Alternatively, dirt and debris can be blown away using compressed air or a hand-held air dryer on the cool setting. A dry chemical sponge may also be used for spot cleaning.